

L149147011

LED E14 Filament DimToWarm Candle
C35x100mm 230V 320Lm 4W 2000-2700K
920-927 360° AC Opal Dimmable

Household, Dim To Warm



General		Energy																												
Eprel registration no	1743773	Operating voltage	230 V																											
Socket	E14	Volt	220..240 V																											
Bulb shape	C35	Frequency	50..60 Hz																											
Width	35.00 mm	Watt	4 W																											
Depth	35.00 mm	Current type	AC																											
Height	100.00 mm	Power factor	0.65																											
Finish	Opal	Energy efficiency class	G																											
Colour	White	Energy consumption	4 W																											
Colour housing	White	Replacement wattage	30 W																											
Body material	Glass	Lamp efficacy	80.00																											
Lifespan	25000 hours	<div>LED</div> <table><tr><td>Filament LED</td><td colspan="2">Yes</td></tr><tr><td>LED type</td><td colspan="2">Ceramic</td></tr><tr><td>Dimm type</td><td colspan="2">Trailing and leading edge</td></tr><tr><td>Number of leds / sticks</td><td colspan="2">4</td></tr><tr><td>Stick length</td><td colspan="2">38 mm</td></tr><tr><td>Stick mounting</td><td colspan="2">Twisted</td></tr><tr><td>Colour consistency SDCM</td><td colspan="2">SDCM6</td></tr><tr><td>Dim to warm</td><td colspan="2">Yes</td></tr><tr><td>Adjustable beam angle</td><td colspan="2">No</td></tr></table>		Filament LED	Yes		LED type	Ceramic		Dimm type	Trailing and leading edge		Number of leds / sticks	4		Stick length	38 mm		Stick mounting	Twisted		Colour consistency SDCM	SDCM6		Dim to warm	Yes		Adjustable beam angle	No	
Filament LED	Yes																													
LED type	Ceramic																													
Dimm type	Trailing and leading edge																													
Number of leds / sticks	4																													
Stick length	38 mm																													
Stick mounting	Twisted																													
Colour consistency SDCM	SDCM6																													
Dim to warm	Yes																													
Adjustable beam angle	No																													
Switches	50000																													
Beam angle	360 °																													
Dimmable	Yes																													
Degree of protection	IP20																													
Net weight	0.009 kg																													
Warranty	2 years																													
Light		<div>Ordering details</div> <table><tr><td>L149147011</td><td>Quantity pc(s)</td><td>EAN</td></tr><tr><td>Single package</td><td>1</td><td>8718739070882</td></tr><tr><td>Inner carton</td><td>10</td><td>18718739070889</td></tr><tr><td>Outer carton</td><td>100</td><td>28718739070886</td></tr></table>		L149147011	Quantity pc(s)	EAN	Single package	1	8718739070882	Inner carton	10	18718739070889	Outer carton	100	28718739070886															
L149147011	Quantity pc(s)			EAN																										
Single package	1			8718739070882																										
Inner carton	10			18718739070889																										
Outer carton	100			28718739070886																										
Kelvin	2000..2700 K																													
Colour temp nr	920..927																													
Stable lumen	320 lm																													
Color Rendering Index (CRI)	93																													