



L149147037

LED E14 Candle C35x105mm 230V 470Lm
5W 2700K 827 150° AC Opal Dimmable

Household, General Dimmable



| General | | Energy | | | | | | | | | | | | | | | | | | | | | | |
|-----------------------------|---------------------------|---|----------------|----------------|----|--|----------|----------|--|-----------|---------------------------|--|-------------------------|---|--|-------------------------|-------|--|-------------|----|--|-----------------------|----|--|
| Eprel registration no | 559272 | Operating voltage | 230 V | | | | | | | | | | | | | | | | | | | | | |
| Socket | E14 | Volt | 220..240 V | | | | | | | | | | | | | | | | | | | | | |
| Bulb shape | C35 | Frequency | 50..60 Hz | | | | | | | | | | | | | | | | | | | | | |
| Width | 35.00 mm | Watt | 5 W | | | | | | | | | | | | | | | | | | | | | |
| Depth | 35.00 mm | Current type | AC | | | | | | | | | | | | | | | | | | | | | |
| Height | 105.00 mm | Power factor | 0.80 | | | | | | | | | | | | | | | | | | | | | |
| Finish | Opal | Energy efficiency class | F | | | | | | | | | | | | | | | | | | | | | |
| Colour | White | Energy consumption | 5 W | | | | | | | | | | | | | | | | | | | | | |
| Colour housing | White | Replacement wattage | 40 W | | | | | | | | | | | | | | | | | | | | | |
| Body material | Polycarbonat | Lamp efficacy | 94.00 | | | | | | | | | | | | | | | | | | | | | |
| Lifespan | 15000 hours | <div>LED</div> <table><tr><td>Filament LED</td><td colspan="2">No</td></tr><tr><td>LED type</td><td colspan="2">SMD 2835</td></tr><tr><td>Dimm type</td><td colspan="2">Trailing and leading edge</td></tr><tr><td>Number of leds / sticks</td><td colspan="2">9</td></tr><tr><td>Colour consistency SDCM</td><td colspan="2">SDCM5</td></tr><tr><td>Dim to warm</td><td colspan="2">No</td></tr><tr><td>Adjustable beam angle</td><td colspan="2">No</td></tr></table> | | Filament LED | No | | LED type | SMD 2835 | | Dimm type | Trailing and leading edge | | Number of leds / sticks | 9 | | Colour consistency SDCM | SDCM5 | | Dim to warm | No | | Adjustable beam angle | No | |
| Filament LED | No | | | | | | | | | | | | | | | | | | | | | | | |
| LED type | SMD 2835 | | | | | | | | | | | | | | | | | | | | | | | |
| Dimm type | Trailing and leading edge | | | | | | | | | | | | | | | | | | | | | | | |
| Number of leds / sticks | 9 | | | | | | | | | | | | | | | | | | | | | | | |
| Colour consistency SDCM | SDCM5 | | | | | | | | | | | | | | | | | | | | | | | |
| Dim to warm | No | | | | | | | | | | | | | | | | | | | | | | | |
| Adjustable beam angle | No | | | | | | | | | | | | | | | | | | | | | | | |
| Switches | 50000 | | | | | | | | | | | | | | | | | | | | | | | |
| Beam angle | 150 ° | | | | | | | | | | | | | | | | | | | | | | | |
| Dimmable | Yes | | | | | | | | | | | | | | | | | | | | | | | |
| Degree of protection | IP20 | | | | | | | | | | | | | | | | | | | | | | | |
| Net weight | 0.033 kg | | | | | | | | | | | | | | | | | | | | | | | |
| Warranty | 3 years | | | | | | | | | | | | | | | | | | | | | | | |
| Light | | Ordering details | | | | | | | | | | | | | | | | | | | | | | |
| Kelvin | 2700 K | L149147037 | Quantity pc(s) | EAN | | | | | | | | | | | | | | | | | | | | |
| Colour temp nr | 827 | Single package | 1 | 8718739056114 | | | | | | | | | | | | | | | | | | | | |
| Stable lumen | 470 lm | Inner carton | 10 | 18718739056111 | | | | | | | | | | | | | | | | | | | | |
| Color Rendering Index (CRI) | 80 | Outer carton | 100 | 28718739056118 | | | | | | | | | | | | | | | | | | | | |

