



L149147037

LED E14 Candle C35x105mm 230V 470Lm
5W 2700K 827 150° AC Opal Dimmable

Household, General Dimmable



General		Energy																						
Eprel registration no	559272	Operating voltage	230 V																					
Socket	E14	Volt	220..240 V																					
Bulb shape	C35	Frequency	50..60 Hz																					
Width	35.00 mm	Watt	5 W																					
Depth	35.00 mm	Current type	AC																					
Height	105.00 mm	Power factor	0.80																					
Finish	Opal	Energy efficiency class	F																					
Colour	White	Energy consumption	5 W																					
Colour housing	White	Replacement wattage	40 W																					
Body material	Polycarbonat	Lamp efficacy	94.00																					
Lifespan	15000 hours	<div>LED</div> <table><tr><td>Filament LED</td><td colspan="2">No</td></tr><tr><td>LED type</td><td colspan="2">SMD 2835</td></tr><tr><td>Dimm type</td><td colspan="2">Trailing and leading edge</td></tr><tr><td>Number of leds / sticks</td><td colspan="2">9</td></tr><tr><td>Colour consistency SDCM</td><td colspan="2">SDCM5</td></tr><tr><td>Dim to warm</td><td colspan="2">No</td></tr><tr><td>Adjustable beam angle</td><td colspan="2">No</td></tr></table>		Filament LED	No		LED type	SMD 2835		Dimm type	Trailing and leading edge		Number of leds / sticks	9		Colour consistency SDCM	SDCM5		Dim to warm	No		Adjustable beam angle	No	
Filament LED	No																							
LED type	SMD 2835																							
Dimm type	Trailing and leading edge																							
Number of leds / sticks	9																							
Colour consistency SDCM	SDCM5																							
Dim to warm	No																							
Adjustable beam angle	No																							
Switches	50000																							
Beam angle	150 °																							
Dimmable	Yes																							
Degree of protection	IP20																							
Net weight	0.033 kg																							
Warranty	3 years																							
Light		Ordering details																						
Kelvin	2700 K	L149147037	Quantity pc(s)	EAN																				
Colour temp nr	827	Single package	1	8718739056114																				
Stable lumen	470 lm	Inner carton	10	18718739056111																				
Color Rendering Index (CRI)	80	Outer carton	100	28718739056118																				

