



PROFESSIONAL
LIGHTING

L151800830

LED Ba15d Tube T18x80mm 230V 840Lm
6W 3000K 830 360° AC/DC Clear
Dimmable

**Marine & Industry, Tubular Compact
Premium**



General	
Eprel registration no	831333
Socket	Ba15d
Bulb shape	T18
Width	18.00 mm
Depth	18.00 mm
Height	80.00 mm
Finish	Clear
Colour	Colourless
Body material	Polycarbonat
Lifespan	25000 hours
Switches	50000
Beam angle	360 °
Dimmable	Yes
Degree of protection	IP20
Net weight	0.025 kg
Warranty	3 years

Energy	
Operating voltage	230 V
Volt	220..240 V
Frequency	50..60 Hz
Watt	6 W
Current type	AC/DC
Power factor	0.9
Energy efficiency class	D
Energy consumption	6 W
Replacement wattage	62 W
Lamp efficacy	140.00

LED	
Filament LED	No
LED type	SMD
Dimm type	Trailing and leading edge
Number of leds / sticks	70
Colour consistency SDCM	SDCM6
Dim to warm	No
Adjustable beam angle	No

Light	
Kelvin	3000 K
Colour temp nr	830
Stable lumen	840 lm
Color Rendering Index (CRI)	80

Ordering details		
L151800830	Quantity pc(s)	EAN
Single package	1	8718739063891
Inner carton	10	18718739063898
Outer carton	100	28718739063895



Pottenbakkerstraat 35, 4871 EP Etten-Leur, The Netherlands | www.spl-lighting.com | info@spl-lighting.com | Telephone +31 (0)76 - 503 77 17
Fax +31 (0)76 501 78 69 | [f splprofessionalighting](#) | [schiefersignaal](#)

25-07-2025