



L151800830

LED Ba15d Tube T18x80mm 230V 840Lm
6W 3000K 830 360° AC/DC Clear
Dimmable

Marine & Industry, Tubular Compact Premium



General		Energy		
Eprel registration no	831333	Operating voltage	230 V	
Socket	Ba15d	Volt	220..240 V	
Bulb shape	T18	Frequency	50..60 Hz	
Width	18.00 mm	Watt	6 W	
Depth	18.00 mm	Current type	AC/DC	
Height	80.00 mm	Power factor	0.9	
Finish	Clear	Energy efficiency class	D	
Colour	Colourless	Energy consumption	6 W	
Body material	Polycarbonat	Lamp efficacy	140.00	
Lifespan	25000 hours	LED		
Switches	50000	Filament LED	No	
Beam angle	360 °	LED type	SMD	
Dimmable	Yes	Dimm type	Trailing and leading edge	
Degree of protection	IP20	Number of leds / sticks	70	
Net weight	0.025 kg	Colour consistency SDCM	SDCM6	
Warranty	3 years	Dim to warm	No	
Light		Adjustable beam angle	No	
Kelvin	3000 K	Ordering details		
Colour temp nr	830	L151800830	Quantity pc(s)	EAN
Stable lumen	840 lm	Single package	1	8718739063891
Color Rendering Index (CRI)	80	Inner carton	10	18718739063898
		Outer carton	100	28718739063895

