

L151801830

LED Ba15d Tube T18x80mm 230V 660Lm
6W 3000K 830 360° AC/DC Opal
Dimmable

Marine & Industry, Tubular Compact Premium



| General | | Energy | | |
|-----------------------------|--------------|-------------------------|---------------------------|----------------|
| Eprel registration no | 831334 | Operating voltage | 230 V | |
| Socket | Ba15d | Volt | 220..240 V | |
| Bulb shape | T18 | Frequency | 50..60 Hz | |
| Width | 18.00 mm | Watt | 6 W | |
| Depth | 18.00 mm | Current type | AC/DC | |
| Height | 80.00 mm | Power factor | 0.9 | |
| Finish | Opal | Energy efficiency class | E | |
| Colour | Colourless | Energy consumption | 6 W | |
| Body material | Polycarbonat | Lamp efficacy | 110.00 | |
| Lifespan | 25000 hours | LED | | |
| Switches | 50000 | Filament LED | No | |
| Beam angle | 360 ° | LED type | SMD | |
| Dimmable | Yes | Dimm type | Trailing and leading edge | |
| Degree of protection | IP20 | Number of leds / sticks | 70 | |
| Net weight | 0.025 kg | Colour consistency SDCM | SDCM6 | |
| Warranty | 3 years | Dim to warm | No | |
| Light | | Adjustable beam angle | No | |
| Kelvin | 3000 K | Ordering details | | |
| Colour temp nr | 830 | L151801830 | Quantity pc(s) | EAN |
| Stable lumen | 660 lm | Single package | 1 | 8718739063907 |
| Color Rendering Index (CRI) | 80 | Inner carton | 10 | 18718739063904 |
| | | Outer carton | 100 | 28718739063901 |