



L151822330

LED Ba15d Tube T18x45mm 230V 250Lm
3W 3000K 830 360° AC Clear Non-
Dimmable

Marine & Industry, Tubular Compact



General	
Eprel registration no	1113040
Socket	Ba15d
Bulb shape	T18
Width	18.00 mm
Depth	18.00 mm
Height	45.00 mm
Finish	Clear
Colour	Colourless
Body material	Polycarbonat
Lifespan	30000 hours
Switches	50000
Beam angle	360 °
Dimmable	No
Degree of protection	IP20
Net weight	0.011 kg
Warranty	2 years

Light	
Kelvin	3000 K
Colour temp nr	830
Stable lumen	250 lm
Color Rendering Index (CRI)	80

Energy	
Operating voltage	230 V
Volt	220..235 V
Frequency	50 Hz
Watt	3 W
Current type	AC
Power factor	0.4
Energy efficiency class	G
Energy consumption	3 W
Replacement wattage	25 W
Lamp efficacy	83.33

LED	
Filament LED	No
LED type	SMD 2835
Dimm type	Non-Dim
Number of leds / sticks	24
Colour consistency SDCM	SDCM3
Dim to warm	No
Adjustable beam angle	No

Ordering details		
L151822330	Quantity pc(s)	EAN
Single package	1	8718739066489
Inner carton	10	18718739066486
Outer carton	100	28718739066483