



L151822330

LED Ba15d Tube T18x45mm 230V 250Lm
3W 3000K 830 360° AC Clear Non-Dimmable

Marine & Industry, Tubular Short



| General | | Energy | | |
|-----------------------------|--------------|-------------------------|----------------|----------------|
| Eprel registration no | 1113040 | Operating voltage | 230 V | |
| Socket | Ba15d | Volt | 220..235 V | |
| Bulb shape | T18 | Frequency | 50 Hz | |
| Width | 18.00 mm | Watt | 3 W | |
| Depth | 18.00 mm | Current type | AC | |
| Height | 45.00 mm | Power factor | 0.4 | |
| Finish | Clear | Energy efficiency class | G | |
| Colour | Colourless | Energy consumption | 3 W | |
| Body material | Polycarbonat | Lamp efficacy | 83.33 | |
| Lifespan | 30000 hours | LED | | |
| Switches | 50000 | Filament LED | No | |
| Beam angle | 360 ° | LED type | SMD 2835 | |
| Dimmable | No | Dimm type | Non-Dim | |
| Degree of protection | IP20 | Number of leds / sticks | 24 | |
| Net weight | 0.011 kg | Colour consistency SDCM | SDCM3 | |
| Warranty | 2 years | Dim to warm | No | |
| Light | | Adjustable beam angle | No | |
| Kelvin | 3000 K | Ordering details | | |
| Colour temp nr | 830 | L151822330 | Quantity pc(s) | EAN |
| Stable lumen | 250 lm | Single package | 1 | 8718739066489 |
| Color Rendering Index (CRI) | 80 | Inner carton | 10 | 18718739066486 |
| | | Outer carton | 100 | 28718739066483 |

