



L151824330

LED Ba15d Tube T18x45mm 10-24V 250Lm
3W 3000K 830 360° DC Clear Non-
Dimmable

Marine & Industry, Tubular VR 10-24V



General	
Eprel registration no	1113043
Socket	Ba15d
Bulb shape	T18
Width	18.00 mm
Depth	18.00 mm
Height	45.00 mm
Finish	Clear
Colour	Colourless
Body material	Polycarbonat
Lifespan	30000 hours
Switches	50000
Beam angle	360 °
Dimmable	No
Degree of protection	IP20
Net weight	0.014 kg
Warranty	2 years

Energy	
Operating voltage	24 V
Volt	10..24 V
Frequency	50..60 Hz
Watt	3 W
Current type	DC
Power factor	1
Energy efficiency class	G
Energy consumption	3 W
Replacement wattage	25 W
Lamp efficacy	83.33

LED	
Filament LED	No
LED type	SMD 2835
Dimm type	Non-Dim
Number of leds / sticks	24
Colour consistency SDCM	SDCM3
Dim to warm	No
Adjustable beam angle	No

Light	
Kelvin	3000 K
Colour temp nr	830
Stable lumen	250 lm
Color Rendering Index (CRI)	80

Ordering details		
L151824330	Quantity pc(s)	EAN
Single package	1	8718739066502
Inner carton	50	18718739066509
Outer carton	1000	28718739066506