PROFESSIONAL LIGHTING

## L151824330

LED Ba15d Tube T18x45mm 10-24V 250Lm 3W 3000K 830 360° DC Clear Non-Dimmable

### Marine & Industry, Tubular VR 10-24V

| General | |
|---|---|
| Eprel registration no | 1113043 |
| Socket | Ba15d |
| Bulb shape | T18 |
| Width | 18.00 mm |
| Depth | 18.00 mm |
| Height | 45.00 mm |
| Finish | Clear |
| Colour | Colourless |
| Body material | Polycarbonat |
| Lifespan | 30000 hours |
| Switches | 50000 |
| Beam angle | 360 ° |
| Dimmable | No |
| Degree of protection | IP20 |
| Net weight | 0.014 kg |
| Warranty | 2 years |

| Light | |
|---|---|
| Kelvin | 3000 K |
| Colour temp nr | 830 |
| Stable lumen | 250 lm |
| Color Rendering Index (CRI) | 80 |

| Energy | |
|---|---|
| Operating voltage | 24 V |
| Volt | 10..24 V |
| Frequency | 50..60 Hz |
| Watt | 3 W |
| Current type | DC |
| Power factor | 1 |
| Energy efficiency class | G |
| Energy consumption | 3 W |
| Lamp efficacy | 83.33 |

| LED | |
|---|---|
| Filament LED | No |
| LED type | SMD 2835 |
| Dimm type | Non-Dim |
| Number of leds / sticks | 24 |
| Colour consistency SDCM | SDCM3 |
| Dim to warm | No |
| Adjustable beam angle | No |

| Ordering details | | |
|---|---|---|
| L151824330 | Quantity pc(s) | EAN |
| Single package | 1 | 8718739066502 |
| Inner carton | 50 | 18718739066509 |
| Outer carton | 1000 | 28718739066506 |

Pottenbakkerstraat 35, 4871 EP Etten-Leur, The Netherlands | www.spl-lighting.com | info@spl-lighting.com | Telephone +31 (0)76 - 503 77 17
Fax +31 (0)76 501 78 69 | splprofessionallighting | schiefersignaal