



## L151924330

LED Ba15s Tube T18x45mm 10-24V 250Lm  
3W 3000K 830 360° DC Clear Non-Dimmable

**Marine & Industry, Tubular VR 10-24V**



General		Energy		
Eprel registration no	1113045	Operating voltage	24 V	
Socket	Ba15s	Volt	10..24 V	
Bulb shape	T18	Frequency	50..60 Hz	
Width	18.00 mm	Watt	3 W	
Depth	18.00 mm	Current type	DC	
Height	45.00 mm	Power factor	1	
Finish	Clear	Energy efficiency class	G	
Colour	Colourless	Energy consumption	3 W	
Body material	Polycarbonat	Lamp efficacy	83.33	
Lifespan	30000 hours	<b>LED</b>		
Switches	50000	Filament LED	No	
Beam angle	360 °	LED type	SMD 2835	
Dimmable	No	Dimm type	Non-Dim	
Degree of protection	IP20	Number of leds / sticks	24	
Net weight	0.011 kg	Colour consistency SDCM	SDCM3	
Warranty	2 years	Dim to warm	No	
<b>Light</b>		Adjustable beam angle	No	
Kelvin	3000 K	<b>Ordering details</b>		
Colour temp nr	830	L151924330	Quantity pc(s)	EAN
Stable lumen	250 lm	Single package	1	8718739066519
Color Rendering Index (CRI)	80	Outer carton	100	28718739066513

