PROFESSIONAL LIGHTING

L152810930

LED Ba15d Tube T29x113mm 230V 850Lm
8W 3000K 930 360° AC/DC Opal
Dimmable

Household, Tubular Premium





General	
Eprel registration no	831336
Socket	Ba15d
Bulb shape	T29
Width	29.00 mm
Depth	29.00 mm
Height	113.00 mm
Finish	Opal
Colour	White
Body material	Polycarbonat
Lifespan	25000 hours
Switches	50000
Beam angle	360 °
Dimmable	Yes
Degree of protection	IP20
Net weight	0.058 kg
Warranty	3 years

Light	
CRI	90
Kelvin	3000 K
Colour temp nr	930
Stable lumen	850 lm

Energy	
Operating voltage	230 V
Volt	220..240 V
Frequency	50..60 Hz
Watt	8 W
Current type	AC/DC
Power factor	0.9
Energy efficiency class	F
Energy consumption	8 W
Lamp efficacy	106.25

LED	
Filament LED	No
LED type	SMD
Dimm type	Trailing and leading edge
Number of leds / sticks	72
Colour consistency SDCM	SDCM6
Dim to warm	No
Adjustable beam angle	No

Ordering details		
L152810930	Quantity pc(s)	EAN
Single package	1	8718739063693
Inner carton	10	18718739063690
Outer carton	100	28718739063697

CE | UK CA

Pottenbakkerstraat 35, 4871 EP Etten-Leur, The Netherlands | www.spl-lighting.com | info@spl-lighting.com | Telephone +31 (0)76 - 503 77 17
Fax +31 (0)76 501 78 69 | splprofessionallighting | schiefersignaal