PROFESSIONAL LIGHTING

L152901930

LED Ba15d Tube T29x113mm 230V 1050Lm
10W 3000K 930 360° AC/DC Opal
Dimmable

Household, Tubular Premium





General	
Eprel registration no	831339
Socket	Ba15d
Bulb shape	T29
Width	29.00 mm
Depth	29.00 mm
Height	113.00 mm
Finish	Opal
Colour	White
Body material	Polycarbonat
Lifespan	25000 hours
Switches	50000
Beam angle	360 °
Dimmable	Yes
Degree of protection	IP20
Net weight	0.059 kg
Warranty	3 years

Light	
CRI	90
Kelvin	3000 K
Colour temp nr	930
Stable lumen	1050 lm

Energy	
Operating voltage	230 V
Volt	220..240 V
Frequency	50..60 Hz
Watt	10 W
Current type	AC/DC
Power factor	0.9
Energy efficiency class	F
Energy consumption	10 W
Lamp efficacy	105.00

LED	
Filament LED	No
LED type	SMD
Dimm type	Trailing and leading edge
Number of leds / sticks	72
Colour consistency SDCM	SDCM6
Dim to warm	No
Adjustable beam angle	No

Ordering details

L152901930	Quantity pc(s)	EAN
Single package	1	8718739063853
Inner carton	10	18718739063850
Outer carton	100	28718739063857

CE | UK CA

Pottenbakkerstraat 35, 4871 EP Etten-Leur, The Netherlands | www.spl-lighting.com | info@spl-lighting.com | Telephone +31 (0)76 - 503 77 17
Fax +31 (0)76 501 78 69 | splprofessionallighting | schiefersignaal