



## L157239830

LED Ba15d Ball G45x80mm 12-60V 250Lm  
3W 3000K 830 160° DC Opal Non-Dimmable

**Marine & Industry, General VR 12-60V Premium**



General		Energy		
Eprel registration no	831340	Volt	12..60 V	
Socket	Ba15d	Frequency	50..60 Hz	
Bulb shape	G45	Watt	3 W	
Width	45.00 mm	Current type	DC	
Depth	45.00 mm	Power factor	1	
Height	80.00 mm	Energy efficiency class	G	
Finish	Opal	Energy consumption	3 W	
Colour	White	Lamp efficacy	83.33	
Colour housing	White	<b>LED</b>		
Body material	Polycarbonat	Filament LED	No	
Lifespan	25000 hours	LED type	SMD	
Switches	50000	Dimm type	Non-Dim	
Beam angle	160 °	Number of leds / sticks	5	
Dimmable	No	Colour consistency SDCM	SDCM5	
Degree of protection	IP20	Dim to warm	No	
Net weight	0.019 kg	Adjustable beam angle	No	
Warranty	3 years	<b>Ordering details</b>		
<b>Light</b>		L157239830	Quantity pc(s)	EAN
Kelvin	3000 K	Single package	1	8718739055483
Colour temp nr	830	Inner carton	10	18718739055480
Stable lumen	250 lm	Outer carton	100	28718739055487
Color Rendering Index (CRI)	82			

