



L157239830

LED Ba15d Ball G45x80mm 12-60V 250Lm
3W 3000K 830 160° DC Opal Non-
Dimmable

**Marine & Industry, General VR 12-60V
Premium**



| General | | Energy | |
|-----------------------------|--------------|-------------------------|--------------------|
| Epel registration no | 831340 | Volt | 12..60 V |
| Socket | Ba15d | Frequency | 50..60 Hz |
| Bulb shape | G45 | Watt | 3 W |
| Width | 45.00 mm | Current type | DC |
| Depth | 45.00 mm | Power factor | 1 |
| Height | 80.00 mm | Energy efficiency class | G |
| Finish | Opal | Energy consumption | 3 W |
| Colour | White | Replacement wattage | 25 W |
| Colour housing | White | Lamp efficacy | 83.33 |
| Body material | Polycarbonat | LED | |
| Lifespan | 25000 hours | Filament LED | No |
| Switches | 50000 | LED type | SMD |
| Beam angle | 160 ° | Dimm type | Non-Dim |
| Dimmable | No | Number of leds / sticks | 5 |
| Degree of protection | IP20 | Colour consistency SDCM | SDCM5 |
| Net weight | 0.019 kg | Dim to warm | No |
| Warranty | 3 years | Adjustable beam angle | No |
| Light | | Ordering details | |
| Kelvin | 3000 K | L157239830 | Quantity pc(s) EAN |
| Colour temp nr | 830 | Single package | 1 8718739055483 |
| Stable lumen | 250 lm | Inner carton | 10 18718739055480 |
| Color Rendering Index (CRI) | 82 | Outer carton | 100 28718739055487 |