PROFESSIONAL LIGHTING

L223864830-1

LED Ba22d Stick T38x105mm 95-265V
640Lm 5W 3000K 830 180° AC/DC Opal
Non-Dimmable

Marine & Industry, Tubular 95-265V





General	
Eprel registration no	2752268
Socket	Ba22d
Bulb shape	T38
Width	38.00 mm
Depth	38.00 mm
Height	105.00 mm
Finish	Opal
Colour	White
Colour housing	White
Body material	Polycarbonat
Lifespan	25000 hours
Switches	15000
Beam angle	180 °
Dimmable	No
Degree of protection	IP20
Net weight	0.037 kg
Warranty	2 years

Light	
CRI	82
Kelvin	3000 K
Colour temp nr	830
Stable lumen	640 lm

Energy	
Volt	95..265 V
Frequency	50..60 Hz
Watt	5 W
Current type	AC/DC
Power factor	0.5
Energy efficiency class	E
Energy consumption	5 W
Lamp efficacy	128.00

LED	
Filament LED	No
LED type	SMD 2835
Dimm type	Non-Dim
Number of leds / sticks	8
Colour consistency SDCM	SDCM5
Dim to warm	No
Adjustable beam angle	No

Ordering details		
L223864830-1	Quantity pc(s)	EAN
Single package	1	8718739070356
Inner carton	10	18718739070353
Outer carton	100	28718739070350

CE | UK CA

Pottenbakkerstraat 35, 4871 EP Etten-Leur, The Netherlands | www.spl-lighting.com | info@spl-lighting.com | Telephone +31 (0)76 - 503 77 17
Fax +31 (0)76 501 78 69 | splprofessionallighting | schiefersignaal