PROFESSIONAL LIGHTING

L224199930

LED Ba22d Stick T41x125mm 95-265V
1180Lm 9W 3000K 830 180° AC/DC Opal
Non-Dimmable

Marine & Industry, Tubular 95-265V







General	
Eprel registration no	1622023
Socket	Ba22d
Bulb shape	T41
Width	41.00 mm
Depth	41.00 mm
Height	125.00 mm
Finish	Opal
Colour	White
Colour housing	White
Body material	Polycarbonat
Lifespan	25000 hours
Switches	15000
Beam angle	180 °
Dimmable	No
Degree of protection	IP20
Net weight	0.038 kg
Warranty	2 years

Light	
CRI	82
Kelvin	3000 K
Colour temp nr	830
Stable lumen	1180 lm

Energy	
Volt	95..265 V
Frequency	50..60 Hz
Watt	9 W
Current type	AC/DC
Power factor	0.5
Energy efficiency class	E
Energy consumption	9 W
Lamp efficacy	131.11

LED	
Filament LED	No
LED type	SMD 2835
Dimm type	Non-Dim
Number of leds / sticks	16
Colour consistency SDCM	SDCM5
Dim to warm	No
Adjustable beam angle	No

Ordering details		
L224199930	Quantity pc(s)	EAN
Single package	1	8718739070363
Inner carton	10	18718739070360
Outer carton	100	28718739070367

CE | UK CA

Pottenbakkerstraat 35, 4871 EP Etten-Leur, The Netherlands | www.spl-lighting.com | info@spl-lighting.com | Telephone +31 (0)76 - 503 77 17
Fax +31 (0)76 501 78 69 | splprofessionallighting | schiefersignaal