



## L224199930

LED Ba22d Stick T41x125mm 95-265V  
1180Lm 9W 3000K 830 180° AC/DC Opal  
Non-Dimmable

## Marine & Industry, Tubular VR 95-265V



General		Energy	
Epel registration no	1622023	Volt	95..265 V
Socket	Ba22d	Frequency	50..60 Hz
Bulb shape	T41	Watt	9 W
Width	41.00 mm	Current type	AC/DC
Depth	41.00 mm	Power factor	0.5
Height	125.00 mm	Energy efficiency class	E
Finish	Opal	Energy consumption	9 W
Colour	White	Replacement wattage	82 W
Colour housing	White	Lamp efficacy	131.11
Body material	Polycarbonat	LED	
Lifespan	25000 hours	Filament LED	No
Switches	15000	LED type	SMD 2835
Beam angle	180 °	Dimm type	Non-Dim
Dimmable	No	Number of leds / sticks	16
Degree of protection	IP20	Colour consistency SDCM	SDCM5
Net weight	0.038 kg	Dim to warm	No
Warranty	2 years	Adjustable beam angle	No
Light		Ordering details	
Kelvin	3000 K	L224199930	Quantity pc(s) EAN
Colour temp nr	830	Single package	1 8718739070363
Stable lumen	1180 lm	Inner carton	10 18718739070360
Color Rendering Index (CRI)	82	Outer carton	100 28718739070367