



L224199930

LED Ba22d Stick T41x125mm 95-265V
1180Lm 9W 3000K 830 180° AC/DC Opal
Non-Dimmable

Marine & Industry, Tubular VR 95-265V



General		Energy		
Eprel registration no	1622023	Volt	95..265 V	
Socket	Ba22d	Frequency	50..60 Hz	
Bulb shape	T41	Watt	9 W	
Width	41.00 mm	Current type	AC/DC	
Depth	41.00 mm	Power factor	0.5	
Height	125.00 mm	Energy efficiency class	E	
Finish	Opal	Energy consumption	9 W	
Colour	White	Lamp efficacy	131.11	
Colour housing	White	LED		
Body material	Polycarbonat	Filament LED	No	
Lifespan	25000 hours	LED type	SMD 2835	
Switches	15000	Dimm type	Non-Dim	
Beam angle	180 °	Number of leds / sticks	16	
Dimmable	No	Colour consistency SDCM	SDCM5	
Degree of protection	IP20	Dim to warm	No	
Net weight	0.038 kg	Adjustable beam angle	No	
Warranty	2 years	Ordering details		
Light		L224199930	Quantity pc(s)	EAN
Kelvin	3000 K	Single package	1	8718739070363
Colour temp nr	830	Inner carton	10	18718739070360
Stable lumen	1180 lm	Outer carton	100	28718739070367
Color Rendering Index (CRI)	82			

