



## L226016830

LED Ba22d GLS A60x115mm 12-60V 810Lm  
10W 3000K 830 220° AC/DC Opal Non-  
Dimmable

**Marine & Industry, General VR 12-60V  
Premium**



| General                     |              | Energy                  |                    |
|-----------------------------|--------------|-------------------------|--------------------|
| Epel registration no        | 2143669      | Volt                    | 12..60 V           |
| Socket                      | Ba22d        | Frequency               | 50..60 Hz          |
| Bulb shape                  | A60          | Watt                    | 10 W               |
| Width                       | 60.00 mm     | Current type            | AC/DC              |
| Depth                       | 60.00 mm     | Power factor            | 0.5                |
| Height                      | 115.00 mm    | Energy efficiency class | G                  |
| Finish                      | Opal         | Energy consumption      | 10 W               |
| Colour                      | White        | Replacement wattage     | 60 W               |
| Colour housing              | White        | Lamp efficacy           | 81.00              |
| Body material               | Polycarbonat | LED                     |                    |
| Lifespan                    | 25000 hours  | Filament LED            | No                 |
| Switches                    | 50000        | LED type                | SMD                |
| Beam angle                  | 220 °        | Dimm type               | Non-Dim            |
| Dimmable                    | No           | Number of leds / sticks | 11                 |
| Degree of protection        | IP20         | Colour consistency SDCM | SDCM6              |
| Net weight                  | 0.043 kg     | Dim to warm             | No                 |
| Warranty                    | 2 years      | Adjustable beam angle   | No                 |
| Light                       |              | Ordering details        |                    |
| Kelvin                      | 3000 K       | L226016830              | Quantity pc(s) EAN |
| Colour temp nr              | 830          | Single package          | 1 8718739076877    |
| Stable lumen                | 810 lm       | Inner carton            | 10 18718739076874  |
| Luminous intensity          | 126 cd       | Outer carton            | 100 28718739076871 |
| Color Rendering Index (CRI) | 80           |                         |                    |

