



L226016830

LED Ba22d GLS A60x115mm 12-60V 810Lm
10W 3000K 830 220° AC/DC Opal Non-Dimmable

Marine & Industry, General VR 12-60V Premium



| General | | Energy | | |
|-----------------------------|--------------|-------------------------|----------------|----------------|
| Eprel registration no | 2143669 | Volt | 12..60 V | |
| Socket | Ba22d | Frequency | 50..60 Hz | |
| Bulb shape | A60 | Watt | 10 W | |
| Width | 60.00 mm | Current type | AC/DC | |
| Depth | 60.00 mm | Power factor | 0.5 | |
| Height | 115.00 mm | Energy efficiency class | G | |
| Finish | Opal | Energy consumption | 10 W | |
| Colour | White | Lamp efficacy | 81.00 | |
| Colour housing | White | LED | | |
| Body material | Polycarbonat | Filament LED | No | |
| Lifespan | 25000 hours | LED type | SMD | |
| Switches | 50000 | Dimm type | Non-Dim | |
| Beam angle | 220 ° | Number of leds / sticks | 11 | |
| Dimmable | No | Colour consistency SDCM | SDCM6 | |
| Degree of protection | IP20 | Dim to warm | No | |
| Net weight | 0.043 kg | Adjustable beam angle | No | |
| Warranty | 2 years | Ordering details | | |
| Light | | L226016830 | Quantity pc(s) | EAN |
| Kelvin | 3000 K | Single package | 1 | 8718739076877 |
| Colour temp nr | 830 | Inner carton | 10 | 18718739076874 |
| Stable lumen | 810 lm | Outer carton | 100 | 28718739076871 |
| Luminous intensity | 126 cd | | | |
| Color Rendering Index (CRI) | 80 | | | |

