



L274199930

LED E27 Stick T41x125mm 95-265V 1180Lm
9W 3000K 830 180° AC Opal Non-Dimmable

Marine & Industry, Tubular VR 95-265V



| General | | Energy | | |
|-----------------------------|--------------|-------------------------|----------------|----------------|
| Eprel registration no | 1622022 | Volt | 95..265 V | |
| Socket | E27 | Frequency | 50..60 Hz | |
| Bulb shape | T41 | Watt | 9 W | |
| Width | 41.00 mm | Current type | AC | |
| Depth | 41.00 mm | Power factor | 0.5 | |
| Height | 125.00 mm | Energy efficiency class | E | |
| Finish | Opal | Energy consumption | 9 W | |
| Colour | White | Lamp efficacy | 131.11 | |
| Colour housing | White | LED | | |
| Body material | Polycarbonat | Filament LED | No | |
| Lifespan | 25000 hours | LED type | SMD 2835 | |
| Switches | 15000 | Dimm type | Non-Dim | |
| Beam angle | 180 ° | Number of leds / sticks | 16 | |
| Dimmable | No | Colour consistency SDCM | SDCM5 | |
| Degree of protection | IP20 | Dim to warm | No | |
| Net weight | 0.043 kg | Adjustable beam angle | No | |
| Warranty | 2 years | Ordering details | | |
| Light | | L274199930 | Quantity pc(s) | EAN |
| Kelvin | 3000 K | Single package | 1 | 8718739070349 |
| Colour temp nr | 830 | Inner carton | 10 | 18718739070346 |
| Stable lumen | 1180 lm | Outer carton | 100 | 28718739070343 |
| Color Rendering Index (CRI) | 82 | | | |

