



L276047037-1

LED E27 GLS A60x105mm 230V 470Lm 5W
2700K 827 200° AC Opal Dimmable

Household, General Dimmable



| General | | Energy | | | | | | | | | | | | | | | |
|-----------------------------|---------------------------|--|----------------|--------------|----|----------|-----|-----------|---------------------------|-------------------------|---|-------------------------|-------|-------------|----|-----------------------|----|
| Eprel registration no | 1132264 | Operating voltage | 230 V | | | | | | | | | | | | | | |
| Socket | E27 | Volt | 220..240 V | | | | | | | | | | | | | | |
| Bulb shape | A60 | Frequency | 50..60 Hz | | | | | | | | | | | | | | |
| Width | 60.00 mm | Watt | 5 W | | | | | | | | | | | | | | |
| Depth | 60.00 mm | Current type | AC | | | | | | | | | | | | | | |
| Height | 105.00 mm | Power factor | 0.5 | | | | | | | | | | | | | | |
| Finish | Opal | Energy efficiency class | F | | | | | | | | | | | | | | |
| Colour | White | Energy consumption | 5 W | | | | | | | | | | | | | | |
| Colour housing | White | Replacement wattage | 40 W | | | | | | | | | | | | | | |
| Body material | PVC | Lamp efficacy | 94.00 | | | | | | | | | | | | | | |
| Lifespan | 15000 hours | <div>LED</div> <table><tr><td>Filament LED</td><td>No</td></tr><tr><td>LED type</td><td>SMD</td></tr><tr><td>Dimm type</td><td>Trailing and leading edge</td></tr><tr><td>Number of leds / sticks</td><td>7</td></tr><tr><td>Colour consistency SDCM</td><td>SDCM6</td></tr><tr><td>Dim to warm</td><td>No</td></tr><tr><td>Adjustable beam angle</td><td>No</td></tr></table> | | Filament LED | No | LED type | SMD | Dimm type | Trailing and leading edge | Number of leds / sticks | 7 | Colour consistency SDCM | SDCM6 | Dim to warm | No | Adjustable beam angle | No |
| Filament LED | No | | | | | | | | | | | | | | | | |
| LED type | SMD | | | | | | | | | | | | | | | | |
| Dimm type | Trailing and leading edge | | | | | | | | | | | | | | | | |
| Number of leds / sticks | 7 | | | | | | | | | | | | | | | | |
| Colour consistency SDCM | SDCM6 | | | | | | | | | | | | | | | | |
| Dim to warm | No | | | | | | | | | | | | | | | | |
| Adjustable beam angle | No | | | | | | | | | | | | | | | | |
| Switches | 30000 | | | | | | | | | | | | | | | | |
| Beam angle | 240 ° | | | | | | | | | | | | | | | | |
| Dimmable | Yes | | | | | | | | | | | | | | | | |
| Degree of protection | IP20 | | | | | | | | | | | | | | | | |
| Net weight | 0.029 kg | | | | | | | | | | | | | | | | |
| Warranty | 2 years | | | | | | | | | | | | | | | | |
| Light | | Ordering details | | | | | | | | | | | | | | | |
| Kelvin | 2700 K | L276047037-1 | Quantity pc(s) | | | | | | | | | | | | | | |
| Colour temp nr | 827 | | EAN | | | | | | | | | | | | | | |
| Stable lumen | 470 lm | Single package | 1 | | | | | | | | | | | | | | |
| Color Rendering Index (CRI) | 80 | Inner carton | 10 | | | | | | | | | | | | | | |
| | | Outer carton | 40 | | | | | | | | | | | | | | |
| | | | 8718739066564 | | | | | | | | | | | | | | |
| | | | 18718739066561 | | | | | | | | | | | | | | |
| | | | 28718739066568 | | | | | | | | | | | | | | |

