



## L276060019

LED E27 Filament GLS A60x108mm 230V  
250Lm 4.5W 1900K 819 360° AC Flame  
Dimmable

### Decorative, Flame



General		Energy																			
Eprel registration no	831401	Operating voltage	230 V																		
Socket	E27	Volt	220..240 V																		
Bulb shape	A60	Frequency	50..60 Hz																		
Width	60.00 mm	Watt	4.5 W																		
Depth	60.00 mm	Current type	AC																		
Height	108.00 mm	Power factor	0.85																		
Finish	Flame	Energy efficiency class	G																		
Colour	Colourless	Energy consumption	5 W																		
Body material	Glass	Replacement wattage	25 W																		
Lifespan	15000 hours	Lamp efficacy	55.56																		
Switches	50000	<div>LED</div> <table><tr><td>Filament LED</td><td>Yes</td></tr><tr><td>LED type</td><td>Ceramic</td></tr><tr><td>Dimm type</td><td>Trailing and leading edge</td></tr><tr><td>Number of leds / sticks</td><td>4</td></tr><tr><td>Stick length</td><td>38 mm</td></tr><tr><td>Stick mounting</td><td>Straight - Top narrow bottom wide</td></tr><tr><td>Colour consistency SDCM</td><td>SDCM6</td></tr><tr><td>Dim to warm</td><td>No</td></tr><tr><td>Adjustable beam angle</td><td>No</td></tr></table>		Filament LED	Yes	LED type	Ceramic	Dimm type	Trailing and leading edge	Number of leds / sticks	4	Stick length	38 mm	Stick mounting	Straight - Top narrow bottom wide	Colour consistency SDCM	SDCM6	Dim to warm	No	Adjustable beam angle	No
Filament LED	Yes																				
LED type	Ceramic																				
Dimm type	Trailing and leading edge																				
Number of leds / sticks	4																				
Stick length	38 mm																				
Stick mounting	Straight - Top narrow bottom wide																				
Colour consistency SDCM	SDCM6																				
Dim to warm	No																				
Adjustable beam angle	No																				
Beam angle	360 °																				
Dimmable	Yes																				
Degree of protection	IP20																				
Net weight	0.035 kg																				
Warranty	2 years																				
Light		<div>Ordering details</div> <table><tr><td>L276060019</td><td>Quantity pc(s)</td><td>EAN</td></tr><tr><td>Single package</td><td>1</td><td>8718739059306</td></tr><tr><td>Inner carton</td><td>10</td><td>18718739059303</td></tr><tr><td>Outer carton</td><td>100</td><td>28718739059300</td></tr></table>		L276060019	Quantity pc(s)	EAN	Single package	1	8718739059306	Inner carton	10	18718739059303	Outer carton	100	28718739059300						
L276060019	Quantity pc(s)			EAN																	
Single package	1			8718739059306																	
Inner carton	10			18718739059303																	
Outer carton	100			28718739059300																	
Kelvin	1900 K																				
Colour temp nr	819																				
Stable lumen	250 lm																				
Color Rendering Index (CRI)	80																				

