



## L277345027-1

LED E27 Filament PC Ball G45x68mm 230V  
130Lm 1.5W 2700K 827 Polycarbonate 360°  
AC Clear Non-Dimmable

**Specials & Projects, Shatterproof  
Polycarbonate**



General		Energy																			
Epel registration no	1318266	Operating voltage	230 V																		
Socket	E27	Volt	220..240 V																		
Bulb shape	G45	Frequency	50..60 Hz																		
Width	45.00 mm	Watt	1.5 W																		
Depth	45.00 mm	Current type	AC																		
Height	68.00 mm	Power factor	0.85																		
Finish	Clear	Energy efficiency class	F																		
Colour	Colourless	Energy consumption	2 W																		
Body material	Polycarbonat	Replacement wattage	14 W																		
Lifespan	25000 hours	Lamp efficacy	86.67																		
Switches	15000	<div>LED</div> <table><tr><td>Filament LED</td><td>Yes</td></tr><tr><td>LED type</td><td>Ceramic</td></tr><tr><td>Dimm type</td><td>Non-Dim</td></tr><tr><td>Number of leds / sticks</td><td>2</td></tr><tr><td>Stick length</td><td>28 mm</td></tr><tr><td>Stick mounting</td><td>Vertical</td></tr><tr><td>Colour consistency SDCM</td><td>SDCM6</td></tr><tr><td>Dim to warm</td><td>No</td></tr><tr><td>Adjustable beam angle</td><td>No</td></tr></table>		Filament LED	Yes	LED type	Ceramic	Dimm type	Non-Dim	Number of leds / sticks	2	Stick length	28 mm	Stick mounting	Vertical	Colour consistency SDCM	SDCM6	Dim to warm	No	Adjustable beam angle	No
Filament LED	Yes																				
LED type	Ceramic																				
Dimm type	Non-Dim																				
Number of leds / sticks	2																				
Stick length	28 mm																				
Stick mounting	Vertical																				
Colour consistency SDCM	SDCM6																				
Dim to warm	No																				
Adjustable beam angle	No																				
Beam angle	360 °																				
Dimmable	No																				
Degree of protection	IP20																				
Net weight	0.012 kg																				
Warranty	2 years																				
<div>Light</div> <table><tr><td>Kelvin</td><td>2700 K</td></tr><tr><td>Colour temp nr</td><td>827</td></tr><tr><td>Stable lumen</td><td>130 lm</td></tr><tr><td>Color Rendering Index (CRI)</td><td>80</td></tr></table>		Kelvin	2700 K	Colour temp nr	827	Stable lumen	130 lm	Color Rendering Index (CRI)	80												
Kelvin	2700 K																				
Colour temp nr	827																				
Stable lumen	130 lm																				
Color Rendering Index (CRI)	80																				
<div>Remark</div> <p>Unbreakable Polycarbonate Body If these LEDs are used outside, their lifespan hence warranty is shortened to one year</p>		<div>Ordering details</div> <table><tr><td>L277345027-1</td><td>Quantity pc(s)</td><td>EAN</td></tr><tr><td>Single package</td><td>1</td><td>8718739067837</td></tr><tr><td>Inner carton</td><td>10</td><td>18718739067834</td></tr><tr><td>Outer carton</td><td>100</td><td>28718739067831</td></tr></table>		L277345027-1	Quantity pc(s)	EAN	Single package	1	8718739067837	Inner carton	10	18718739067834	Outer carton	100	28718739067831						
L277345027-1	Quantity pc(s)	EAN																			
Single package	1	8718739067837																			
Inner carton	10	18718739067834																			
Outer carton	100	28718739067831																			