



PROFESSIONAL
LIGHTING

L277355127

LED E27 Filament PC GLS A55x100mm
230V 320Lm 3.5W 2700K 827
Polycarbonate 360° AC Clear Non-
Dimmable

Specials & Projects, Shatterproof
Polycarbonate



General		Energy																			
Epel registration no	543792	Operating voltage	230 V																		
Socket	E27	Volt	220..240 V																		
Bulb shape	A55	Frequency	50..60 Hz																		
Width	55.00 mm	Watt	3.5 W																		
Depth	55.00 mm	Current type	AC																		
Height	100.00 mm	Power factor	0.75																		
Finish	Clear	Energy efficiency class	F																		
Colour	Colourless	Energy consumption	4 W																		
Body material	Polycarbonat	Replacement wattage	30 W																		
Lifespan	15000 hours	Lamp efficacy	91.43																		
Switches	50000	<div>LED</div> <table><tr><td>Filament LED</td><td>Yes</td></tr><tr><td>LED type</td><td>Ceramic</td></tr><tr><td>Dimm type</td><td>Non-Dim</td></tr><tr><td>Number of leds / sticks</td><td>4</td></tr><tr><td>Stick length</td><td>38 mm</td></tr><tr><td>Stick mounting</td><td>Straight</td></tr><tr><td>Colour consistency SDCM</td><td>SDCM6</td></tr><tr><td>Dim to warm</td><td>No</td></tr><tr><td>Adjustable beam angle</td><td>No</td></tr></table>		Filament LED	Yes	LED type	Ceramic	Dimm type	Non-Dim	Number of leds / sticks	4	Stick length	38 mm	Stick mounting	Straight	Colour consistency SDCM	SDCM6	Dim to warm	No	Adjustable beam angle	No
Filament LED	Yes																				
LED type	Ceramic																				
Dimm type	Non-Dim																				
Number of leds / sticks	4																				
Stick length	38 mm																				
Stick mounting	Straight																				
Colour consistency SDCM	SDCM6																				
Dim to warm	No																				
Adjustable beam angle	No																				
Beam angle	360 °																				
Dimmable	No																				
Degree of protection	IP20																				
Net weight	0.012 kg																				
Warranty	2 years																				

Light		
Kelvin	2700 K	
Colour temp nr	827	
Stable lumen	320 lm	
Color Rendering Index (CRI)	80	

Remark		
Unbreakable Polycarbonate Body If these LEDs are used outside, their lifespan hence warranty is shortened to one year		

Ordering details		
L277355127	Quantity pc(s)	EAN
Single package	1	8718739064423
Inner carton	10	18718739064420
Outer carton	100	28718739064427



Pottenbakkerstraat 35, 4871 EP Etten-Leur, The Netherlands | www.spl-lighting.com | info@spl-lighting.com | Telephone +31 (0)76 - 503 77 17
Fax +31 (0)76 501 78 69 | [f splprofessionallighting](#) | [schiefersignaal](#)



25-07-2025