

L279514003

LED E27 Filament Flex DH Globe
G95x135mm 230V 120Lm 5W 2200K 822
360° AC Smoke Dimmable

Decorative, Flex Double Helix



General		Energy																			
Eprel registration no	766113	Operating voltage	230 V																		
Socket	E27	Volt	220..240 V																		
Bulb shape	G95	Frequency	50..60 Hz																		
Width	95.00 mm	Watt	5 W																		
Depth	95.00 mm	Current type	AC																		
Height	135.00 mm	Power factor	0.85																		
Finish	Clear	Energy consumption	5 W																		
Colour	Smoke	Replacement wattage	13 W																		
Body material	Glass	Lamp efficacy	24.00																		
Lifespan	15000 hours	<div>LED</div> <table><tr><td>Filament LED</td><td>Yes</td></tr><tr><td>LED type</td><td>Flex</td></tr><tr><td>Dimm type</td><td>Trailing and leading edge</td></tr><tr><td>Number of leds / sticks</td><td>2</td></tr><tr><td>Stick length</td><td>130 mm</td></tr><tr><td>Stick mounting</td><td>Spiral Double helix</td></tr><tr><td>Colour consistency SDCM</td><td>SDCM6</td></tr><tr><td>Dim to warm</td><td>No</td></tr><tr><td>Adjustable beam angle</td><td>No</td></tr></table>		Filament LED	Yes	LED type	Flex	Dimm type	Trailing and leading edge	Number of leds / sticks	2	Stick length	130 mm	Stick mounting	Spiral Double helix	Colour consistency SDCM	SDCM6	Dim to warm	No	Adjustable beam angle	No
Filament LED	Yes																				
LED type	Flex																				
Dimm type	Trailing and leading edge																				
Number of leds / sticks	2																				
Stick length	130 mm																				
Stick mounting	Spiral Double helix																				
Colour consistency SDCM	SDCM6																				
Dim to warm	No																				
Adjustable beam angle	No																				
Switches	30000																				
Beam angle	360 °																				
Dimmable	Yes																				
Degree of protection	IP20																				
Net weight	0.067 kg																				
Warranty	2 years																				
Light		<div>Ordering details</div> <table><tr><td>L279514003</td><td>Quantity pc(s)</td><td>EAN</td></tr><tr><td>Single package</td><td>1</td><td>8718739065260</td></tr><tr><td>Inner carton</td><td>5</td><td>18718739065267</td></tr><tr><td>Outer carton</td><td>50</td><td>28718739065264</td></tr></table>		L279514003	Quantity pc(s)	EAN	Single package	1	8718739065260	Inner carton	5	18718739065267	Outer carton	50	28718739065264						
L279514003	Quantity pc(s)			EAN																	
Single package	1			8718739065260																	
Inner carton	5			18718739065267																	
Outer carton	50			28718739065264																	
Kelvin	2200 K																				
Colour temp nr	822																				
Stable lumen	120 lm																				
Color Rendering Index (CRI)	80																				