



L480103640

LED PLL 2G11 4 pin Glass T43x416mm 230V
18W 2300Lm 840 AC 4000K (repl.
PLL36W) Opal Non-Dimmable

Marine & Industry, Led PLL 2G11 4pin



| General | | Energy | |
|-----------------------------|-------------|-------------------------|----------------|
| Eprel registration no | 2039270 | Operating voltage | 230 V |
| Socket | 2G11 | Volt | 220..240 V |
| Bulb shape | T43 | Frequency | 50..60 Hz |
| Width | 43.00 mm | Watt | 18 W |
| Depth | 23.00 mm | Current type | AC |
| Height | 416.00 mm | Power factor | 0.9 |
| Finish | Opal | Energy efficiency class | E |
| Colour | White | Energy consumption | 18 W |
| Colour housing | White | Replacement wattage | 142 W |
| Body material | Glass | Lamp efficacy | 127.78 |
| Lifespan | 25000 hours | | |
| Switches | 15000 | LED | |
| Beam angle | 270 ° | Filament LED | No |
| Dimmable | No | LED type | SMD 2835 |
| Degree of protection | IP20 | Dimm type | Non-Dim |
| Net weight | 0.128 kg | Number of leds / sticks | 96 |
| Warranty | 2 years | Colour consistency SDCM | SDCM6 |
| | | Dim to warm | No |
| | | Adjustable beam angle | No |
| Light | | Ordering details | |
| Kelvin | 4000 K | L480103640 | Quantity pc(s) |
| Colour temp nr | 840 | | EAN |
| Stable lumen | 2300 lm | Single package | 1 |
| Color Rendering Index (CRI) | 80 | Inner carton | 10 |
| | | Outer carton | 100 |