



L480104030

LED PLL 2G11 4 pin Glass T44x530mm 230V
20W 2500Lm 830 AC 3000K (repl.
PLL40W) Opal Non-Dimmable

Marine & Industry, PLL 2G11 4pin



General		Energy		
Eprel registration no	2039272	Operating voltage	230 V	
Socket	2G11	Volt	220..240 V	
Bulb shape	T44	Frequency	50..60 Hz	
Width	44.00 mm	Watt	20 W	
Depth	23.00 mm	Current type	AC	
Height	530.00 mm	Power factor	0.9	
Finish	Opal	Energy efficiency class	E	
Colour	White	Energy consumption	20 W	
Colour housing	White	Lamp efficacy	125.00	
Body material	Glass	LED		
Lifespan	30000 hours	Filament LED	No	
Switches	15000	LED type	SMD 2835	
Beam angle	270 °	Dimm type	Non-Dim	
Dimmable	No	Number of leds / sticks	120	
Degree of protection	IP20	Colour consistency SDCM	SDCM6	
Net weight	0.149 kg	Dim to warm	No	
Warranty	2 years	Adjustable beam angle	No	
Light		Ordering details		
Kelvin	3000 K	L480104030	Quantity pc(s)	EAN
Colour temp nr	830	Single package	1	8718739071537
Stable lumen	2500 lm	Inner carton	10	18718739071534
Color Rendering Index (CRI)	80	Outer carton	100	28718739071531

