



## L480104040

LED PLL 2G11 4 pin Glass T43x537mm 230V  
20W 2600Lm 840 AC 4000K (repl.  
PLL40W) Opal Non-Dimmable

### Marine & Industry, Led PLL 2G11 4pin



General		Energy		
Eprel registration no	2039273	Operating voltage	230 V	
Socket	2G11	Volt	220..240 V	
Bulb shape	T43	Frequency	50..60 Hz	
Width	43.00 mm	Watt	20 W	
Depth	23.00 mm	Current type	AC	
Height	537.00 mm	Power factor	0.9	
Finish	Opal	Energy efficiency class	E	
Colour	White	Energy consumption	20 W	
Colour housing	White	Replacement wattage	157 W	
Body material	Glass	Lamp efficacy	130.00	
Lifespan	25000 hours			
Switches	15000	LED		
Beam angle	270 °	Filament LED	No	
Dimmable	No	LED type	SMD 2835	
Degree of protection	IP20	Dimm type	Non-Dim	
Net weight	0.148 kg	Number of leds / sticks	120	
Warranty	2 years	Colour consistency SDCM	SDCM6	
		Dim to warm	No	
		Adjustable beam angle	No	
Light		Ordering details		
Kelvin	4000 K	L480104040	Quantity pc(s)	EAN
Colour temp nr	840	Single package	1	8718739071544
Stable lumen	2600 lm	Inner carton	10	18718739071541
Color Rendering Index (CRI)	80	Outer carton	100	28718739071548