



L480104065

LED PLL 2G11 4 pin Glass T43x537mm 230V
20W 2600Lm 865 AC 6500K (repl.
PLL40W) Opal Non-Dimmable

Marine & Industry, Led PLL 2G11 4pin



| General | | Energy | | | | | | | | | | | | | | | |
|-----------------------------|-------------|---|----------------|--------------|----|----------|----------|-----------|---------|-------------------------|-----|-------------------------|-------|-------------|----|-----------------------|----|
| Eprel registration no | 2039274 | Operating voltage | 230 V | | | | | | | | | | | | | | |
| Socket | 2G11 | Volt | 220..240 V | | | | | | | | | | | | | | |
| Bulb shape | T43 | Frequency | 50..60 Hz | | | | | | | | | | | | | | |
| Width | 43.00 mm | Watt | 20 W | | | | | | | | | | | | | | |
| Depth | 23.00 mm | Current type | AC | | | | | | | | | | | | | | |
| Height | 537.00 mm | Power factor | 0.9 | | | | | | | | | | | | | | |
| Finish | Opal | Energy efficiency class | E | | | | | | | | | | | | | | |
| Colour | White | Energy consumption | 20 W | | | | | | | | | | | | | | |
| Colour housing | White | Replacement wattage | 157 W | | | | | | | | | | | | | | |
| Body material | Glass | Lamp efficacy | 130.00 | | | | | | | | | | | | | | |
| Lifespan | 25000 hours | <div>LED</div> <table><tr><td>Filament LED</td><td>No</td></tr><tr><td>LED type</td><td>SMD 2835</td></tr><tr><td>Dimm type</td><td>Non-Dim</td></tr><tr><td>Number of leds / sticks</td><td>120</td></tr><tr><td>Colour consistency SDCM</td><td>SDCM6</td></tr><tr><td>Dim to warm</td><td>No</td></tr><tr><td>Adjustable beam angle</td><td>No</td></tr></table> | | Filament LED | No | LED type | SMD 2835 | Dimm type | Non-Dim | Number of leds / sticks | 120 | Colour consistency SDCM | SDCM6 | Dim to warm | No | Adjustable beam angle | No |
| Filament LED | No | | | | | | | | | | | | | | | | |
| LED type | SMD 2835 | | | | | | | | | | | | | | | | |
| Dimm type | Non-Dim | | | | | | | | | | | | | | | | |
| Number of leds / sticks | 120 | | | | | | | | | | | | | | | | |
| Colour consistency SDCM | SDCM6 | | | | | | | | | | | | | | | | |
| Dim to warm | No | | | | | | | | | | | | | | | | |
| Adjustable beam angle | No | | | | | | | | | | | | | | | | |
| Switches | 15000 | | | | | | | | | | | | | | | | |
| Beam angle | 270 ° | | | | | | | | | | | | | | | | |
| Dimmable | No | | | | | | | | | | | | | | | | |
| Degree of protection | IP20 | | | | | | | | | | | | | | | | |
| Net weight | 0.148 kg | | | | | | | | | | | | | | | | |
| Warranty | 2 years | | | | | | | | | | | | | | | | |
| Light | | Ordering details | | | | | | | | | | | | | | | |
| Kelvin | 6500 K | L480104065 | Quantity pc(s) | | | | | | | | | | | | | | |
| Colour temp nr | 865 | | EAN | | | | | | | | | | | | | | |
| Stable lumen | 2600 lm | Single package | 1 | | | | | | | | | | | | | | |
| Color Rendering Index (CRI) | 80 | Inner carton | 10 | | | | | | | | | | | | | | |
| | | Outer carton | 100 | | | | | | | | | | | | | | |