



## L480105540

LED PLL 2G11 4 pin Glass T44x530mm 230V  
24W 3300Lm 840 AC 4000K (repl.  
PLL55W) Opal Non-Dimmable

### Marine & Industry, PLL 2G11 4pin



General		Energy	
Eprel registration no	1869518	Operating voltage	230 V
Socket	2G11	Volt	220..240 V
Bulb shape	T44	Frequency	50..60 Hz
Width	44.00 mm	Watt	24 W
Depth	23.00 mm	Current type	AC
Height	530.00 mm	Power factor	0.5
Finish	Opal	Energy efficiency class	D
Colour	White	Energy consumption	24 W
Colour housing	White	Lamp efficacy	137.50
Body material	Glass		
Lifespan	30000 hours	LED	
Switches	15000	Filament LED	No
Beam angle	270 °	LED type	SMD 2835
Dimmable	No	Dimm type	Non-Dim
Degree of protection	IP20	Number of leds / sticks	120
Net weight	0.149 kg	Colour consistency SDCM	SDCM6
Warranty	2 years	Dim to warm	No
		Adjustable beam angle	No
Light		Ordering details	
Kelvin	4000 K	L480105540	Quantity pc(s) EAN
Colour temp nr	840	Single package	1 8718739071575
Stable lumen	3300 lm	Inner carton	10 18718739071572
Color Rendering Index (CRI)	80	Outer carton	100 28718739071579

