



## L480105540

LED PLL 2G11 4 pin Glass T44x530mm 230V  
24W 3300Lm 840 AC 4000K (repl.  
PLL55W) Opal Non-Dimmable

### Marine & Industry, PLL 2G11 4pin



| General                     |             | Energy                  |                |                |
|-----------------------------|-------------|-------------------------|----------------|----------------|
| Eprel registration no       | 1869518     | Operating voltage       | 230 V          |                |
| Socket                      | 2G11        | Volt                    | 220..240 V     |                |
| Bulb shape                  | T44         | Frequency               | 50..60 Hz      |                |
| Width                       | 44.00 mm    | Watt                    | 24 W           |                |
| Depth                       | 23.00 mm    | Current type            | AC             |                |
| Height                      | 530.00 mm   | Power factor            | 0.5            |                |
| Finish                      | Opal        | Energy efficiency class | D              |                |
| Colour                      | White       | Energy consumption      | 24 W           |                |
| Colour housing              | White       | Lamp efficacy           | 137.50         |                |
| Body material               | Glass       | <b>LED</b>              |                |                |
| Lifespan                    | 30000 hours | Filament LED            | No             |                |
| Switches                    | 15000       | LED type                | SMD 2835       |                |
| Beam angle                  | 270 °       | Dimm type               | Non-Dim        |                |
| Dimmable                    | No          | Number of leds / sticks | 120            |                |
| Degree of protection        | IP20        | Colour consistency SDCM | SDCM6          |                |
| Net weight                  | 0.149 kg    | Dim to warm             | No             |                |
| Warranty                    | 2 years     | Adjustable beam angle   | No             |                |
| Light                       |             | Ordering details        |                |                |
| Kelvin                      | 4000 K      | L480105540              | Quantity pc(s) | EAN            |
| Colour temp nr              | 840         | Single package          | 1              | 8718739071575  |
| Stable lumen                | 3300 lm     | Inner carton            | 10             | 18718739071572 |
| Color Rendering Index (CRI) | 80          | Outer carton            | 100            | 28718739071579 |

