



L480105540

LED PLL 2G11 4 pin Glass T43x537mm 230V
24W 3300Lm 840 AC 4000K (repl.
PLL55W) Opal Non-Dimmable

Marine & Industry, Led PLL 2G11 4pin



| General | | Energy | | |
|-----------------------------|-------------|-------------------------|----------------|----------------|
| Eprel registration no | 1869518 | Operating voltage | 230 V | |
| Socket | 2G11 | Volt | 220..240 V | |
| Bulb shape | T43 | Frequency | 50..60 Hz | |
| Width | 43.00 mm | Watt | 24 W | |
| Depth | 23.00 mm | Current type | AC | |
| Height | 537.00 mm | Power factor | 0.5 | |
| Finish | Opal | Energy efficiency class | D | |
| Colour | White | Energy consumption | 24 W | |
| Colour housing | White | Replacement wattage | 192 W | |
| Body material | Glass | Lamp efficacy | 137.50 | |
| Lifespan | 25000 hours | | | |
| Switches | 15000 | LED | | |
| Beam angle | 270 ° | Filament LED | No | |
| Dimmable | No | LED type | SMD 2835 | |
| Degree of protection | IP20 | Dimm type | Non-Dim | |
| Net weight | 0.148 kg | Number of leds / sticks | 120 | |
| Warranty | 2 years | Colour consistency SDCM | SDCM6 | |
| | | Dim to warm | No | |
| | | Adjustable beam angle | No | |
| Light | | Ordering details | | |
| Kelvin | 4000 K | L480105540 | Quantity pc(s) | EAN |
| Colour temp nr | 840 | Single package | 1 | 8718739071575 |
| Stable lumen | 3300 lm | Inner carton | 10 | 18718739071572 |
| Color Rendering Index (CRI) | 80 | Outer carton | 100 | 28718739071579 |