PROFESSIONAL LIGHTING

L480105540

LED PLL 2G11 4 pin Glass T44x530mm 230V 24W 3300Lm 840 AC 4000K (repl. PLL55W) Opal Non-Dimmable

Marine & Industry, PLL 2G11 4pin AC





General	
Eprel registration no	1869518
Socket	2G11
Bulb shape	T44
Width	44.00 mm
Depth	23.00 mm
Height	530.00 mm
Finish	Opal
Colour	White
Colour housing	White
Body material	Glass
Lifespan	30000 hours
Switches	15000
Beam angle	270 °
Dimmable	No
Degree of protection	IP20
Net weight	0.161 kg
Warranty	2 years

Energy	
Operating voltage	230 V
Volt	220..240 V
Frequency	50..60 Hz
Watt	24 W
Current type	AC
Power factor	0.5
Energy efficiency class	D
Energy consumption	24 W
Lamp efficacy	137.50

LED	
Filament LED	No
LED type	SMD 2835
Dimm type	Non-Dim
Number of leds / sticks	120
Colour consistency SDCM	SDCM6
Dim to warm	No
Adjustable beam angle	No

Light	
CRI	80
Kelvin	4000 K
Colour temp nr	840
Stable lumen	3300 lm

Ordering details		
L480105540	Quantity pc(s)	EAN
Single package	1	8718739071575
Inner carton	10	18718739071572
Outer carton	100	28718739071579

CE | UK CA

Pottenbakkerstraat 35, 4871 EP Etten-Leur, The Netherlands | www.spl-lighting.com | info@spl-lighting.com | Telephone +31 (0)76 - 503 77 17
Fax +31 (0)76 501 78 69 | splprofessionallighting | schiefersignaal