



L480105565

LED PLL 2G11 4 pin Glass T43x537mm 230V
24W 3300Lm 865 AC 6500K (repl.
PLL55W) Opal Non-Dimmable

Marine & Industry, Led PLL 2G11 4pin



| General | |
|-----------------------|-------------|
| Eprel registration no | 2088075 |
| Socket | 2G11 |
| Bulb shape | T43 |
| Width | 43.00 mm |
| Depth | 23.00 mm |
| Height | 537.00 mm |
| Finish | Opal |
| Colour | White |
| Colour housing | White |
| Body material | Glass |
| Lifespan | 25000 hours |
| Switches | 15000 |
| Beam angle | 270 ° |
| Dimmable | No |
| Degree of protection | IP20 |
| Net weight | 0.148 kg |
| Warranty | 2 years |

| Energy | |
|-------------------------|------------|
| Operating voltage | 230 V |
| Volt | 220..240 V |
| Frequency | 50..60 Hz |
| Watt | 24 W |
| Current type | AC |
| Power factor | 0.9 |
| Energy efficiency class | D |
| Energy consumption | 24 W |
| Replacement wattage | 192 W |
| Lamp efficacy | 137.50 |

| LED | |
|-------------------------|----------|
| Filament LED | No |
| LED type | SMD 2835 |
| Dimm type | Non-Dim |
| Number of leds / sticks | 120 |
| Colour consistency SDCM | SDCM6 |
| Dim to warm | No |
| Adjustable beam angle | No |

| Light | |
|-----------------------------|---------|
| Kelvin | 6500 K |
| Colour temp nr | 865 |
| Stable lumen | 3300 lm |
| Color Rendering Index (CRI) | 80 |

| Ordering details | | |
|------------------|----------------|----------------|
| L480105565 | Quantity pc(s) | EAN |
| Single package | 1 | 8718739071582 |
| Inner carton | 10 | 18718739071589 |
| Outer carton | 100 | 28718739071586 |