



L480300765

LED PLS 2G7 4 pin Glass T30x137mm 230V
3W 390Lm 865 AC 6500K (repl. PLS7W)
Opal Non-Dimmable

Marine & Industry, Led PLS 2G7 4pin



| General | |
|-----------------------|-------------|
| Eprel registration no | 2039287 |
| Socket | 2G7 |
| Bulb shape | T30 |
| Width | 30.00 mm |
| Depth | 20.80 mm |
| Height | 137.00 mm |
| Finish | Opal |
| Colour | White |
| Colour housing | White |
| Body material | Glass |
| Lifespan | 25000 hours |
| Switches | 15000 |
| Beam angle | 270 ° |
| Dimmable | No |
| Degree of protection | IP20 |
| Net weight | 0.032 kg |
| Warranty | 2 years |

| Energy | | |
|-------------------------|----------------|----------------|
| Operating voltage | 230 V | |
| Volt | 220..240 V | |
| Frequency | 50..60 Hz | |
| Watt | 3 W | |
| Current type | AC | |
| Power factor | 0.9 | |
| Energy efficiency class | E | |
| Energy consumption | 3 W | |
| Replacement wattage | 35 W | |
| Lamp efficacy | 130.00 | |
| LED | | |
| Filament LED | No | |
| LED type | SMD 2835 | |
| Dimm type | Non-Dim | |
| Number of leds / sticks | 24 | |
| Colour consistency SDCM | SDCM6 | |
| Dim to warm | No | |
| Adjustable beam angle | No | |
| Ordering details | | |
| L480300765 | Quantity pc(s) | EAN |
| Single package | 1 | 8718739073333 |
| Inner carton | 10 | 18718739073330 |
| Outer carton | 100 | 28718739073337 |

| Light | |
|-----------------------------|--------|
| Kelvin | 6500 K |
| Colour temp nr | 865 |
| Stable lumen | 390 lm |
| Color Rendering Index (CRI) | 80 |