PROFESSIONAL LIGHTING

L480301140

LED PLS 2G7 4 pin Glass T37x205mm 230V
5W 730Lm 840 AC 4000K (repl. PLS11W)
Opal Non-Dimmable

Marine & Industry, PLS 2G7 4pin AC





General	
Eprel registration no	1869522
Socket	2G7
Bulb shape	T37
Width	37.00 mm
Depth	21.00 mm
Height	205.00 mm
Finish	Opal
Colour	White
Colour housing	White
Body material	Glass
Lifespan	25000 hours
Switches	15000
Beam angle	270 °
Dimmable	No
Degree of protection	IP20
Net weight	0.043 kg
Warranty	2 years

Energy	
Operating voltage	230 V
Volt	220..240 V
Frequency	50..60 Hz
Watt	5 W
Current type	AC
Power factor	0.5
Energy efficiency class	D
Energy consumption	5 W
Lamp efficacy	146.00

LED	
Filament LED	No
LED type	SMD 2835
Dimm type	Non-Dim
Number of leds / sticks	60
Colour consistency SDCM	SDCM6
Dim to warm	No
Adjustable beam angle	No

Light	
CRI	80
Kelvin	4000 K
Colour temp nr	840
Stable lumen	730 lm

Ordering details		
L480301140	Quantity pc(s)	EAN
Single package	1	8718739071865
Inner carton	10	18718739071862
Outer carton	100	28718739071869

CE | UK CA

Pottenbakkerstraat 35, 4871 EP Etten-Leur, The Netherlands | www.spl-lighting.com | info@spl-lighting.com | Telephone +31 (0)76 - 503 77 17
Fax +31 (0)76 501 78 69 | splprofessionallighting | schiefersignaal