



## L480401830

LED PLC G24D 2 pin Glass T34x148mm  
230V 6W 850Lm 830 AC 3000K (repl.  
PLD18W) Opal Non-Dimmable

### Marine & Industry, Led PLC G24D 2pin



General	
Epel registration no	2039292
Socket	G24d
Bulb shape	T34
Width	34.00 mm
Depth	35.00 mm
Height	148.00 mm
Finish	Opal
Colour	White
Colour housing	White
Body material	Glass
Lifespan	25000 hours
Switches	15000
Beam angle	270 °
Dimmable	No
Degree of protection	IP20
Net weight	0.064 kg
Warranty	2 years

Energy	
Operating voltage	230 V
Volt	220..240 V
Frequency	50..60 Hz
Watt	6 W
Current type	AC
Power factor	0.9
Energy efficiency class	D
Energy consumption	6 W
Replacement wattage	63 W
Lamp efficacy	141.67

LED	
Filament LED	No
LED type	SMD 2835
Dimm type	Non-Dim
Number of leds / sticks	48
Colour consistency SDCM	SDCM6
Dim to warm	No
Adjustable beam angle	No

Light	
Kelvin	3000 K
Colour temp nr	830
Stable lumen	850 lm
Color Rendering Index (CRI)	80

Ordering details		
L480401830	Quantity pc(s)	EAN
Single package	1	8718739073340
Inner carton	10	18718739073347
Outer carton	100	28718739073344