



L480401830

LED PLC G24d 2 pin Glass T34x143mm
230V 6W 850Lm 830 AC+CCG 3000K (repl.
PLD18W) Opal Non-Dimmable

Marine & Industry, PLC G24d 2pin



| General | | Energy | | |
|-----------------------------|-------------|-------------------------|----------------|----------------|
| Eprel registration no | 2039292 | Operating voltage | 230 V | |
| Socket | G24d | Volt | 220..240 V | |
| Bulb shape | T34 | Frequency | 50..60 Hz | |
| Width | 34.00 mm | Watt | 6 W | |
| Depth | 34.00 mm | Current type | AC | |
| Height | 143.00 mm | Power factor | 0.9 | |
| Finish | Opal | Energy efficiency class | D | |
| Colour | White | Energy consumption | 6 W | |
| Colour housing | White | Lamp efficacy | 141.67 | |
| Body material | Glass | LED | | |
| Lifespan | 30000 hours | Filament LED | No | |
| Switches | 15000 | LED type | SMD 2835 | |
| Beam angle | 270 ° | Dimm type | Non-Dim | |
| Dimmable | No | Number of leds / sticks | 48 | |
| Degree of protection | IP20 | Colour consistency SDCM | SDCM6 | |
| Net weight | 0.062 kg | Dim to warm | No | |
| Warranty | 2 years | Adjustable beam angle | No | |
| Light | | Ordering details | | |
| Kelvin | 3000 K | L480401830 | Quantity pc(s) | EAN |
| Colour temp nr | 830 | Single package | 1 | 8718739073340 |
| Stable lumen | 850 lm | Inner carton | 10 | 18718739073347 |
| Color Rendering Index (CRI) | 80 | Outer carton | 100 | 28718739073344 |

