



## L480401830

LED PLC G24D 2 pin Glass T34x148mm  
230V 6W 850Lm 830 AC 3000K (repl.  
PLD18W) Opal Non-Dimmable

### Marine & Industry, Led PLC G24D 2pin



| General               |             |
|-----------------------|-------------|
| Eprel registration no | 2039292     |
| Socket                | G24d        |
| Bulb shape            | T35         |
| Width                 | 34.00 mm    |
| Depth                 | 35.00 mm    |
| Height                | 148.00 mm   |
| Finish                | Opal        |
| Colour                | White       |
| Colour housing        | White       |
| Body material         | Glass       |
| Lifespan              | 25000 hours |
| Switches              | 15000       |
| Beam angle            | 270 °       |
| Dimmable              | No          |
| Degree of protection  | IP20        |
| Net weight            | 0.064 kg    |
| Warranty              | 2 years     |

| Energy                  |                |                |
|-------------------------|----------------|----------------|
| Operating voltage       | 230 V          |                |
| Volt                    | 220..240 V     |                |
| Frequency               | 50..60 Hz      |                |
| Watt                    | 6 W            |                |
| Current type            | AC             |                |
| Power factor            | 0.9            |                |
| Energy efficiency class | D              |                |
| Energy consumption      | 6 W            |                |
| Replacement wattage     | 63 W           |                |
| Lamp efficacy           | 141.67         |                |
| LED                     |                |                |
| Filament LED            | No             |                |
| LED type                | SMD 2835       |                |
| Dimm type               | Non-Dim        |                |
| Number of leds / sticks | 48             |                |
| Colour consistency SDCM | SDCM6          |                |
| Dim to warm             | No             |                |
| Adjustable beam angle   | No             |                |
| Ordering details        |                |                |
| L480401830              | Quantity pc(s) | EAN            |
| Single package          | 1              | 8718739073340  |
| Inner carton            | 10             | 18718739073347 |
| Outer carton            | 100            | 28718739073344 |

| Light                       |        |
|-----------------------------|--------|
| Kelvin                      | 3000 K |
| Colour temp nr              | 830    |
| Stable lumen                | 850 lm |
| Color Rendering Index (CRI) | 80     |