



## L480401840

LED PLC G24D 2 pin Glass T34x148mm  
230V 6W 880Lm 840 AC 4000K (repl.  
PLD18W) Opal Non-Dimmable

### Marine & Industry, Led PLC G24D 2pin



General	
Eprel registration no	2039293
Socket	G24d
Bulb shape	T35
Width	34.00 mm
Depth	35.00 mm
Height	148.00 mm
Finish	Opal
Colour	White
Colour housing	White
Body material	Glass
Lifespan	25000 hours
Switches	15000
Beam angle	270 °
Dimmable	No
Degree of protection	IP20
Net weight	0.064 kg
Warranty	2 years

Energy		
Operating voltage	230 V	
Volt	220..240 V	
Frequency	50..60 Hz	
Watt	6 W	
Current type	AC	
Power factor	0.9	
Energy efficiency class	D	
Energy consumption	6 W	
Replacement wattage	64 W	
Lamp efficacy	146.67	
LED		
Filament LED	No	
LED type	SMD 2835	
Dimm type	Non-Dim	
Number of leds / sticks	48	
Colour consistency SDCM	SDCM6	
Dim to warm	No	
Adjustable beam angle	No	
Ordering details		
L480401840	Quantity pc(s)	EAN
Single package	1	8718739071896
Inner carton	10	18718739071893
Outer carton	100	28718739071890

Light	
Kelvin	4000 K
Colour temp nr	840
Stable lumen	880 lm
Color Rendering Index (CRI)	80