



L480401865

LED PLC G24D 2 pin Glass T34x148mm
230V 6W 880Lm 865 AC 6500K (repl.
PLD18W) Opal Non-Dimmable

Marine & Industry, Led PLC G24D 2pin



| General | | Energy | |
|-----------------------------|-------------|-------------------------|--------------------|
| Epel registration no | 2039294 | Operating voltage | 230 V |
| Socket | G24d | Volt | 220..240 V |
| Bulb shape | T35 | Frequency | 50..60 Hz |
| Width | 34.00 mm | Watt | 6 W |
| Depth | 35.00 mm | Current type | AC |
| Height | 148.00 mm | Power factor | 0.9 |
| Finish | Opal | Energy efficiency class | D |
| Colour | White | Energy consumption | 6 W |
| Colour housing | White | Replacement wattage | 64 W |
| Body material | Glass | Lamp efficacy | 146.67 |
| Lifespan | 25000 hours | LED | |
| Switches | 15000 | Filament LED | No |
| Beam angle | 270 ° | LED type | SMD 2835 |
| Dimmable | No | Dimm type | Non-Dim |
| Degree of protection | IP20 | Number of leds / sticks | 48 |
| Net weight | 0.064 kg | Colour consistency SDCM | SDCM6 |
| Warranty | 2 years | Dim to warm | No |
| | | Adjustable beam angle | No |
| Light | | Ordering details | |
| Kelvin | 6500 K | L480401865 | Quantity pc(s) EAN |
| Colour temp nr | 865 | Single package | 1 8718739072084 |
| Stable lumen | 880 lm | Inner carton | 10 18718739072081 |
| Color Rendering Index (CRI) | 80 | Outer carton | 100 28718739072088 |