PROFESSIONAL LIGHTING

L480402630

LED PLC G24d 2 pin Glass T34x168mm
230V 9W 1280Lm 830 AC+CCG 3000K
(repl. PLD26W) Opal Non-Dimmable

Marine & Industry, PLC G24d 2pin AC+CCG





General	
Eprel registration no	1869523
Socket	G24d
Bulb shape	T34
Width	34.00 mm
Depth	34.00 mm
Height	168.00 mm
Finish	Opal
Colour	White
Colour housing	White
Body material	Glass
Lifespan	25000 hours
Switches	15000
Beam angle	270 °
Dimmable	No
Degree of protection	IP20
Net weight	0.072 kg
Warranty	2 years

Energy	
Operating voltage	230 V
Volt	220..240 V
Frequency	50..60 Hz
Watt	9 W
Current type	AC
Power factor	0.5
Energy efficiency class	D
Energy consumption	9 W
Lamp efficacy	142.22

LED	
Filament LED	No
LED type	SMD 2835
Dimm type	Non-Dim
Number of leds / sticks	72
Colour consistency SDCM	SDCM6
Dim to warm	No
Adjustable beam angle	No

Light	
CRI	80
Kelvin	3000 K
Colour temp nr	830
Stable lumen	1280 lm

Ordering details		
L480402630	Quantity pc(s)	EAN
Single package	1	8718739071902
Inner carton	10	18718739071909
Outer carton	100	28718739071906

CE | UK CA

Pottenbakkerstraat 35, 4871 EP Etten-Leur, The Netherlands | www.spl-lighting.com | info@spl-lighting.com | Telephone +31 (0)76 - 503 77 17
Fax +31 (0)76 501 78 69 | splprofessionallighting | schiefersignaal