



L480402640

LED PLC G24D 2 pin Glass T34x168mm
230V 9W 1360Lm 840 AC 4000K (repl.
PLD26W) Opal Non-Dimmable

Marine & Industry, Led PLC G24D 2pin



| General | | Energy | |
|-----------------------------|-------------|-------------------------|--------------------|
| Epel registration no | 1869524 | Operating voltage | 230 V |
| Socket | G24d | Volt | 220..240 V |
| Bulb shape | T34 | Frequency | 50..60 Hz |
| Width | 34.00 mm | Watt | 9 W |
| Depth | 35.00 mm | Current type | AC |
| Height | 168.00 mm | Power factor | 0.5 |
| Finish | Opal | Energy efficiency class | D |
| Colour | White | Energy consumption | 9 W |
| Colour housing | White | Replacement wattage | 91 W |
| Body material | Glass | Lamp efficacy | 151.11 |
| Lifespan | 25000 hours | LED | |
| Switches | 15000 | Filament LED | No |
| Beam angle | 270 ° | LED type | SMD 2835 |
| Dimmable | No | Dimm type | Non-Dim |
| Degree of protection | IP20 | Number of leds / sticks | 72 |
| Net weight | 0.073 kg | Colour consistency SDCM | SDCM6 |
| Warranty | 2 years | Dim to warm | No |
| | | Adjustable beam angle | No |
| Light | | Ordering details | |
| Kelvin | 4000 K | L480402640 | Quantity pc(s) EAN |
| Colour temp nr | 840 | Single package | 1 8718739071919 |
| Stable lumen | 1360 lm | Inner carton | 10 18718739071916 |
| Color Rendering Index (CRI) | 80 | Outer carton | 100 28718739071913 |