



## L480402665

LED PLC G24d 2 pin Glass T34x168mm  
230V 9W 1360Lm 865 AC+CCG 6500K  
(repl. PLD26W) Opal Non-Dimmable

### Marine & Industry, PLC G24d 2pin



General		Energy		
Eprel registration no	2039295	Operating voltage	230 V	
Socket	G24d	Volt	220..240 V	
Bulb shape	T34	Frequency	50..60 Hz	
Width	34.00 mm	Watt	9 W	
Depth	34.00 mm	Current type	AC	
Height	168.00 mm	Power factor	0.9	
Finish	Opal	Energy efficiency class	D	
Colour	White	Energy consumption	9 W	
Colour housing	White	Lamp efficacy	151.11	
Body material	Glass	<b>LED</b>		
Lifespan	25000 hours	Filament LED	No	
Switches	15000	LED type	SMD 2835	
Beam angle	270 °	Dimm type	Non-Dim	
Dimmable	No	Number of leds / sticks	72	
Degree of protection	IP20	Colour consistency SDCM	SDCM6	
Net weight	0.072 kg	Dim to warm	No	
Warranty	2 years	Adjustable beam angle	No	
Light		Ordering details		
Kelvin	6500 K	L480402665	Quantity pc(s)	EAN
Colour temp nr	865	Single package	1	8718739072091
Stable lumen	1360 lm	Inner carton	10	18718739072098
Color Rendering Index (CRI)	80	Outer carton	100	28718739072095

