



L480402665

LED PLC G24d 2 pin Glass T34x168mm
230V 9W 1360Lm 865 AC+CCG 6500K
(repl. PLD26W) Opal Non-Dimmable

Marine & Industry, PLC G24d 2pin



General		Energy	
Eprel registration no	2039295	Operating voltage	230 V
Socket	G24d	Volt	220..240 V
Bulb shape	T34	Frequency	50..60 Hz
Width	34.00 mm	Watt	9 W
Depth	34.00 mm	Current type	AC
Height	168.00 mm	Power factor	0.9
Finish	Opal	Energy efficiency class	D
Colour	White	Energy consumption	9 W
Colour housing	White	Lamp efficacy	151.11
Body material	Glass	LED	
Lifespan	25000 hours	Filament LED	No
Switches	15000	LED type	SMD 2835
Beam angle	270 °	Dimm type	Non-Dim
Dimmable	No	Number of leds / sticks	72
Degree of protection	IP20	Colour consistency SDCM	SDCM6
Net weight	0.072 kg	Dim to warm	No
Warranty	2 years	Adjustable beam angle	No
Light		Ordering details	
Kelvin	6500 K	L480402665	Quantity pc(s) EAN
Colour temp nr	865	Single package	1 8718739072091
Stable lumen	1360 lm	Inner carton	10 18718739072098
Color Rendering Index (CRI)	80	Outer carton	100 28718739072095

