



L480501840

LED PLC G24Q 4 pin Glass T34x148mm
230V 6W 880Lm 840 AC 4000K (repl.
PLDE18W) Opal Non-Dimmable

Marine & Industry, Led PLC G24Q 4pin



General		Energy		
Eprel registration no	2039298	Operating voltage	230 V	
Socket	G24q	Volt	220..240 V	
Bulb shape	T35	Frequency	50..60 Hz	
Width	34.00 mm	Watt	6 W	
Depth	35.00 mm	Current type	AC	
Height	148.00 mm	Power factor	0.9	
Finish	Opal	Energy efficiency class	D	
Colour	White	Energy consumption	6 W	
Colour housing	White	Replacement wattage	64 W	
Body material	Glass	Lamp efficacy	146.67	
Lifespan	25000 hours			
Switches	15000	LED		
Beam angle	270 °	Filament LED	No	
Dimmable	No	LED type	SMD 2835	
Degree of protection	IP20	Dimm type	Non-Dim	
Net weight	0.064 kg	Number of leds / sticks	48	
Warranty	2 years	Colour consistency SDCM	SDCM6	
		Dim to warm	No	
		Adjustable beam angle	No	
		Ordering details		
		L480501840	Quantity pc(s)	EAN
		Single package	1	8718739071933
		Inner carton	10	18718739071930
		Outer carton	100	28718739071937