



## L480501840

LED PLC G24q 4 pin Glass T34x143mm  
230V 6W 880Lm 840 AC 4000K (repl.  
PLDE18W) Opal Non-Dimmable

### Marine & Industry, PLC G24q 4pin



General		Energy	
Eprel registration no	2039298	Operating voltage	230 V
Socket	G24q	Volt	220..240 V
Bulb shape	T34	Frequency	50..60 Hz
Width	34.00 mm	Watt	6 W
Depth	34.00 mm	Current type	AC
Height	143.00 mm	Power factor	0.9
Finish	Opal	Energy efficiency class	D
Colour	White	Energy consumption	6 W
Colour housing	White	Lamp efficacy	146.67
Body material	Glass	<b>LED</b>	
Lifespan	30000 hours	Filament LED	No
Switches	15000	LED type	SMD 2835
Beam angle	270 °	Dimm type	Non-Dim
Dimmable	No	Number of leds / sticks	48
Degree of protection	IP20	Colour consistency SDCM	SDCM6
Net weight	0.062 kg	Dim to warm	No
Warranty	2 years	Adjustable beam angle	No
<b>Light</b>		<b>Ordering details</b>	
Kelvin	4000 K	L480501840	Quantity pc(s)
Colour temp nr	840	Single package	1
Stable lumen	880 lm	Inner carton	10
Color Rendering Index (CRI)	80	Outer carton	100
			EAN
			8718739071933
			18718739071930
			28718739071937

