



L480501865

LED PLC G24Q 4 pin Glass T34x148mm
230V 6W 880Lm 865 AC 6500K (repl.
PLDE18W) Opal Non-Dimmable

Marine & Industry, Led PLC G24Q 4pin



| General | |
|----------------------|-------------|
| Epel registration no | 2039300 |
| Socket | G24q |
| Bulb shape | T34 |
| Width | 34.00 mm |
| Depth | 35.00 mm |
| Height | 148.00 mm |
| Finish | Opal |
| Colour | White |
| Colour housing | White |
| Body material | Glass |
| Lifespan | 25000 hours |
| Switches | 15000 |
| Beam angle | 270 ° |
| Dimmable | No |
| Degree of protection | IP20 |
| Net weight | 0.064 kg |
| Warranty | 2 years |

| Energy | | |
|-------------------------|----------------|----------------|
| Operating voltage | 230 V | |
| Volt | 220..240 V | |
| Frequency | 50..60 Hz | |
| Watt | 6 W | |
| Current type | AC | |
| Power factor | 0.9 | |
| Energy efficiency class | D | |
| Energy consumption | 6 W | |
| Replacement wattage | 64 W | |
| Lamp efficacy | 146.67 | |
| LED | | |
| Filament LED | No | |
| LED type | SMD 2835 | |
| Dimm type | Non-Dim | |
| Number of leds / sticks | 48 | |
| Colour consistency SDCM | SDCM6 | |
| Dim to warm | No | |
| Adjustable beam angle | No | |
| Ordering details | | |
| L480501865 | Quantity pc(s) | EAN |
| Single package | 1 | 8718739071940 |
| Inner carton | 10 | 18718739071947 |
| Outer carton | 100 | 28718739071944 |

| Light | |
|-----------------------------|--------|
| Kelvin | 6500 K |
| Colour temp nr | 865 |
| Stable lumen | 880 lm |
| Color Rendering Index (CRI) | 80 |